

# Moose F Waterborne Alkyd Emulsion Paint

*Breathable, durable, matte wood paint*



## Technical information

Moose F is a moisture-regulating wood paint that ensures that the surface can continue to breathe. The colors are totally matte and metameric. The paint penetrates strongly into the wood, so that - if applied properly - it hardly peels. The paint is very pleasant to use, does not smell and is easy to maintain.

**Composition:** contains oil of vegetable origin, inorganic fillers, organic emulsifiers, thickeners, pigment and water. Titanium oxide is used for light colours.

**Application:** all types of wood, both indoors and outdoors. Also applicable on wallpaper, plasterboard, terracotta, non-alkaline concrete or stone (with primer). Small metal surfaces can be painted.

**New work:** remove any dirt and dust with a damp cloth. Degrease where necessary. Light pre-sanding improves the result with smooth new wood. Dilute if necessary. Apply two coats.

No primer required.

**Processing temperature:** do not apply outside below approx. 12 °C. Dilute well at temperatures above 25 °C. Avoid exposure to moisture and water until fully cured.

**Drying time:** depending on temperature and humidity. At 20 °C and low humidity (40%) dust dry after 3 hours, paintable after 6 hours and cured after 48-72 hours. Drying times are longer at lower temperatures and higher humidity.

**Consumption:** depending on the substrate 5 m<sup>2</sup> per liter for two layers. Deviations of 20% are possible.

**Reprocessing an already painted surface:** remove the old paint if necessary. The underlying layer must not be able to flake later, must be matt, coarse and free of grease.

**Maintenance period:** 5 years on average, depending on the circumstances. If there is no detachment of the paint, then cleaning and overpainting is sufficient. Sanding is not necessary. After this, a period of 7 years is normal.

**Use brush or spray:** dilute before spraying (approx. 10%), depending on nozzle and pressure.

**Dilute:** with 5-10% water.

**Cleaning:** Clean brushes, work materials and clothing with soap and water. If necessary, rinse brushes with benzene.

**Mix well before use:** make sure that the paint is applied well, including in cracks and seams. Usually 2 coats give an opaque result. Light colors and highly absorbent substrates may require 3 coats. Avoid applying thick layers! Dilute with water if necessary.

**Gloss category:** completely matte. Maximum layer thickness: 100

**Store:** dry and slightly below room temperature (5-15 °C). Avoid exposure to temperatures below 5°C.

**Shelf life:** unopened at least 2 years.

**Mass:** 35%±3

**Volume:** 23%±2

**Density:** 1.1-1.3 Kg/l

**Recommended layer thickness:** 35 µm

Contains a minimal amount of preservation (see packaging).

VOC < 3 g/l Cat A/d  
(EU standard 2010: 130 g/l)

A dried out paint bucket can go with the residual waste. It is more environmentally friendly to take wet paint residues to the environmental station.



Witte Paal 304A, 1742 LD Schagen  
The Netherlands



Moose Färg is developed and produced in Sweden.

SIMPLY GOOD FOR WOOD

WWW.MOOSEFARG.COM